



| Health | 1 |
|------------------------|---|
| Fire | 3 |
| Reactivity | 0 |
| Personal Protection | Н |

Material Safety Data Sheet 1-Butanol MSDS

| Section 1: Chemical Product and Company Identification | | | |
|--|--|--|--|
| Product Name: 1-Butanol | Contact Information: | | |
| Catalog Codes: SLB3157, SLB1489 | Sciencelab.com, Inc. 14025 Smith Rd. | | |
| CAS#: 71-36-3 | Houston, Texas 77396 | | |
| RTECS: EO1400000 | US Sales: 1-800-901-7247 International Sales: 1-281-441-4400 | | |
| TSCA: TSCA 8(b) inventory: 1-Butanol | Order Online: ScienceLab.com | | |
| Cl#: Not applicable. | CHEMTREC (24HR Emergency Telephone), call: 1-800-424-9300 | | |
| Synonym: Propylcarbinol | | | |
| Chemical Name: N-Butyl alcohol | International CHEMTREC, call: 1-703-527-3887 For non-emergency assistance, call: 1-281-441-4400 | | |
| Chemical Formula: CH3(CH2)2CH2OH | | | |

Section 2: Composition and Information on Ingredients

| Composition: | | | |
|--------------|---------|-------------|--|
| Name | CAS # | % by Weight | |
| {1-}Butanol | 71-36-3 | 100 | |

Toxicological Data on Ingredients: 1-Butanol: ORAL (LD50): Acute: 790 mg/kg [Rat.]. DERMAL (LD50): Acute: 3400 mg/kg [Rabbit.].

Section 3: Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of skin contact (irritant, permeator), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (sensitizer). Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 343°C (649.4°F)

Flash Points: CLOSED CUP: 28.9°C (84°F). OPEN CUP: 36.1°C (97°F) (Cleveland).

Flammable Limits: LOWER: 1.4% UPPER: 11.2%

Products of Combustion: These products are carbon oxides (CO, CO2).

Fire Hazards in Presence of Various Substances:

Highly flammable in presence of open flames and sparks. Flammable in presence of heat, of oxidizing materials, of reducing materials, of combustible materials.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Special Remarks on Fire Hazards: May form explosive mixtures with air. CAUTION: MAY BURN WITH NEAR INVISIBLE FLAME

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large Spill:

Flammable liquid.

Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents.

Storage:

Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

CEIL: 152 (mg/m3)

Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Liquid. (Z)

Odor: Vinous. (Slight.)

Taste: Not available.

Molecular Weight: 74.12g/mole

Color: Colorless.

pH (1% soln/water): Not available.

Boiling Point: 117.7°C (243.9°F)

Melting Point: -89.5°C (-129.1°F)

Critical Temperature: Not available.

Specific Gravity: 0.81(Water = 1)

Vapor Pressure: 0.6 kPa (@ 20°C)

Vapor Density: 2.55 (Air = 1)

Volatility: Not available.

Odor Threshold: 1.2 ppm

Water/Oil Dist. Coeff.: Not available.

lonicity (in Water): Not available.

Dispersion Properties: See solubility in water, methanol, diethyl ether, n-octanol.

Solubility:

Easily soluble in methanol, diethyl ether. Partially soluble in cold water, hot water, n-octanol.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Not available.

Incompatibility with various substances:

Highly reactive with oxidizing agents, reducing agents. Slightly reactive to reactive with organic materials, acids, alkalis.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 790 mg/kg [Rat.]. Acute dermal toxicity (LD50): 3400 mg/kg [Rabbit.]. Acute toxicity of the vapor (LC50): 8000 4 hours [Rat.].

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans:

Very hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation. Slightly hazardous in case of skin contact (sensitizer).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Can cause gastrointestinal disturbances.

Special Remarks on other Toxic Effects on Humans: Exposure can cause nausea, headache and vomiting.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Section 14: Transport Information

DOT Classification: CLASS 3: Flammable liquid.

Identification: : Butanol UNNA: UN1120 PG: III

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

Pennsylvania RTK: 1-Butanol Massachusetts RTK: 1-Butanol TSCA 8(b) inventory: 1-Butanol

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:

WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC).

DSCL (EEC): R10- Flammable. R22- Harmful if swallowed. R38- Irritating to skin. R41- Risk of serious damage to eyes.

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 3

Reactivity: 0

Personal Protection: h

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 3

Reactivity: 0

Specific hazard:

Protective Equipment: Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

Section 16: Other Information

References: -Manufacturer's Material Safety Data Sheet.

Other Special Considerations: Not available.

Created: 10/10/2005 08:15 PM

Last Updated: 11/06/2008 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.