Material Safety Data Sheet



Bug Away

Section 1. Chemical product and company identification

Trade name	: Bug Away
Product use	: Cleaning product
Supplier	: Ecolab Inc.Vehicle Care Division 370 N. Wabasha Street St. Paul, MN 55102 1-877-ECOWASH
Code	: 908272-01
Date of issue	: 04-October-2007
	EMERGENCY HEALTH INFORMATION: 1-800-328-0026 Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

Name	CAS number	<u>% by weight</u>
sodium hydroxide	1310-73-2	2
xylenesulfonic acid, sodium salt	1300-72-7	1 - 5
disodium metasilicate	6834-92-0	1 - 5
alcohols, c9-11, ethoxylated	68439-46-3	1 - 5
acetic acid, (ethylenedinitrilo)tetra-, tetrasodium salt	64-02-8	1 - 5
alcohols, c12-16, ethoxylated	68551-12-2	1 - 5
amines, coco alkyldimethyl, n-oxides	61788-90-7	1 - 5

Section 3. Hazards identification

Emergency : overview	DANGER!
	CAUSES EYE AND SKIN BURNS. CAUSES SEVERE RESPIRATORY TRACT IRRITATION. HARMFUL IF SWALLOWED.
	Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Potential acute health e	ffects
Eyes :	Corrosive to eyes.
Skin :	Corrosive to the skin.
Inhalation :	Severely irritating to the respiratory system.
Ingestion :	Harmful if swallowed. Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

Section 4. First aid measures

: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.
: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
: Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire fighting measures

Flash point Fire-fighting media and instructions		> 100°C Use an extinguishing agent suitable for the surrounding fire.
Special protective equipment for fire-fighters	:	Dike liquid for later disposal. No specific hazard. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions	: Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.
Environmental precautions	 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling	: Do not ingest. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Storage	 Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above the following temperature: 50°C

Section 8. Exposure controls, personal protection

Engineering meas	ure	 Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide eyewash and safety shower in area if contact or splash hazard exists.
Personal protection	<u>n :</u>	
Eyes	:	Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.
Hands	:	Use chemical-resistant, impervious gloves.
Skin	:	Use synthetic apron, other protective equipment as necessary to prevent skin contact.
Respiratory	:	Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.
<u>Name</u>		Exposure limits
sodium hydroxide		ACGIH TLV (United States, 1/2006).
		CEIL: 2 mg/m ³
		OSHA PEL (United States, 11/2006).
		TWA: 2 mg/m³ 8 hour(s).

•		Liquid. [Liquid.] Blue.
Odor	:	Faint odor.
рН	:	12 to 13.5 [Conc. (% w/w): 100%]
Specific gravity	:	1.1 to 1.135

Section 10. Stability and reactivity

Stability	: The product is stable.
Reactivity	: Reactive with acids.
-	Slightly reactive to reactive with metals.

Section 11. Toxicological information

Potential acute health effects

Eyes Skin : Corrosive to eyes.

- : Corrosive to the skin.
- Inhalation : Severely irritating to the respiratory system.
- Ingestion : Harmful if swallowed. Causes burns to mouth, throat and stomach.

Potential chronic health effects

Chronic effects on humans : Contains material which causes damage to the following organs: lungs, upper respiratory tract.

Section 12. Ecological information

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

: Unused product is D002 (Corrosive)

classification

Waste

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	UN3266	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide , Sodium metasilicate)	8	111	Not available.

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification	: Corrosive material Target organ effects
U.S. Federal regulations	: SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.
TSCA 8(b) inventory	: All materials are listed or exempt.
California Prop. 65	: No products were found.

Section 16. Other information

Hazardous Material Information System (U.S.A.)	:	Health	¥	3
		Flammability		0
		Physical hazards		0
Date of issue Responsible name	:	04-October-2007. Regulatory Affairs		

Responsible name Date of previous issue <u>Notice to reader</u>

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.

: No previous validation.